



CUTE PLUS

Self priming Mini Monobloc Pumpset



CUTE PLUS

Self priming Mini Monobloc Pumpset

Technical Data

• Pump size : 25 x 25 mm Capacity : up to 58 LPM Head : up to 36 mtrs

Power : up to 1.0 HP (0.75 kW)

 Temperature : Ambient • Liquid : Clear water : 2800 rpm Speed • Starting Method: CSR

Applications:

- Pumping of water to overhead tank
- Drinking water supply
- Ornamental fountains
- Farmhouses

Features:

- Self priming
- Single phase operations
- Compact and sleek design
- Wide voltage range
- Fitted with Thermal Overload Protector for safety
- Suction lift up to 6m possible
- High quality Brass forged impeller and mechanical seal
- Highly Reliable



Performance Chart (Power Supply: 240 V, 50 Hz)

S. no	Pump Model	Motor Ratings	Starting Method	Pipe Size Suc x Del.		Total head in metres									
						6	9	12	15	18	21	24	27	30	36
		HP(kW)		mm		0									
1	CUTE PLUS	0.50 (0.37)	CSR	25 X 25	LPM	35	31	28	23	20	15	12	6	-	-
2	CUTE PLUS I	1.0 (0.75)	CSR	25 X 25		58	51	47	42	37	33	28	23	20	10