



MULTISUB

Vertical Multistage Openwell Pumpset



E-Warranty QR Code



* Selected models only



Pumps Made in India
with trusted German Technology

MULTISUB

Vertical Multistage Openwell Pumpset

Technical Data :

- Pipe Size : 32 mm
- Capacity : up to 111 lpm
- Head : up to 75 m
- Power : up to 1.5 HP
- Voltage : 160-260 V
- Temperature : Ambient
- Speed : 2900 rpm

Applications :

- Irrigation in horticulture and agriculture
- Water supply for High-rise buildings
- Domestic and community water supplies
- Sprinkler and drip irrigation

Benefits:

• Wide Voltage Design :

The motor is designed to withstand wide voltage fluctuations from 160 to 260 volts and reduce motor burning at low voltage.

• Longer and Trouble-Free Life :

High-grade engineering materials like graded cast iron components, stainless steel shafts, noryl impellers, bronze bushings, and heavy-duty carbon and SS thrust plates

- The product is supplied with a control panel, which provides motor protection and has easy installation.



Performance Chart :

Power supply : 240V, 50 Hz, Single Phase

S. no	Pump Model	HP	Starting Method	Del. Size mm	Total head in metres								
					10	20	30	40	50	60	65	70	75
					Discharge in LPM								
1	MULTISUB 10-08	1.0	CSCR	32	105	93	81	67	48	23	-	-	-
2	MULTISUB 15-10	1.5	CSCR	32	111	100	89	78	66	52	44	32	17

Subject to technical modification without prior notice.