



PERISTAR SZX

Self Priming Monobloc Pumpset



E-Warranty QR Code



* Selected models only



Pumps Made in India
with trusted German Technology

PERISTAR SZ X

Self Priming Monobloc Pumpset

Technical Data:

- Capacity : up to 48 LPM
- Head : up to 54 m
- Power : up to 1.5 HP (1.1 kW)
- Temperature : Ambient
- Liquid : Clear water
- Speed : 2800 rpm
- Starting Method : CSR

Applications :

- Car washing
- Residential flats, bungalows
- Water circulation in solar systems
- Gardening and Irrigation
- Domestic water supply

Features:

- Stainless Steel shaft
- TEFC enclosure
- Fitted with Thermal Overload Protector for safety
- Suction lift up to 8 m
- Dynamically balanced Rotor for longer bearing life and vibration free smooth operation
- Robust Ball Bearings sealed for long life

Performance Chart (Power Supply : 240 V, 50 Hz)

| S. no | Pump Model | Motor Ratings | Body | Pipe Size Suc x Del. | Total head in Meters | | | | | | | | | | | | | |
|-------|-----------------|---------------|-----------|----------------------|----------------------|----|----|----|----|----|----|----|----|----|----|----|----|----|
| | | | | | | | | | | | | | | | | | | |
| | | HP | | mm | 6 | 9 | 12 | 15 | 18 | 21 | 24 | 27 | 30 | 32 | 36 | 42 | 48 | 54 |
| 1 | PERISTAR SZ 05X | 0.5 | Alu Extru | 25 X 25 | LPM | 29 | 27 | 23 | 20 | 17 | 13 | 8 | - | - | - | - | - | - |
| 2 | PERISTAR SZ 07X | 0.75 | Alu Extru | 25 X 25 | | 31 | 29 | 27 | 24 | 22 | 19 | 18 | 14 | 11 | 7 | - | - | - |
| 3 | PERISTAR SZ 10X | 1.0 | Alu Extru | 25 X 25 | | 33 | 31 | 29 | 26 | 24 | 22 | 19 | 17 | 13 | 12 | 8 | - | - |
| 4 | PERISTAR SZ 15X | 1.5 | Alu Extru | 25 X 25 | | 48 | 47 | 46 | 45 | 43 | 42 | 40 | 38 | 36 | 35 | 32 | 26 | 19 |



Subject to technical modification without prior notice.