



# PERISTAR V

## Self Priming Monobloc Pumpset



E-Warranty QR Code



PERISTAR VE II Plus



PERISTAR VE II

\* Selected models only



**Pumps Made in India**  
with trusted German Technology

# PERISTAR V

## Self Priming Monobloc Pumpset

### Technical Data

- Pump size : 25 x 25 mm
- Capacity : up to 45 LPM
- Head : up to 39 m
- Power : up to 1.0 HP (0.75 kW)
- Temperature : Ambient
- Liquid : Clear water
- Speed : 2900 rpm
- Starting Method : CSR

### Applications :

- Lawn sprinklers
- Residential flats, bungalows, recreation clubs, car wash
- Garden & fountains
- Water supply to overhead tanks
- Domestic water supply

### Features:

- Robust and sturdy design
- High quality mechanical seal for long life
- Fitted with Thermal Overload Protector for safety
- Brass forged impellers for smooth operation
- Suction lift up to 8 m
- Capacitor start and run (PSC) type design eliminates centrifugal switch
- Robust Ball Bearings sealed for long life



### Performance Chart (Power Supply : 240 V, 50 Hz)

S. no	Pump Model	Motor Ratings	Motor Body	Pipe Size Suc x Del.	Total head in meters											
					6	9	12	15	18	21	24	27	30	33	36	39
		HP		mm	Discharge in LPM											
1	PERISTAR VE II	0.5	Alu. Extu	25x25	45	43	40	37	34	31	28	24	20	-	-	-
2	PERISTAR V II	0.5	C.I.	25x25	45	43	40	37	34	31	28	24	20	-	-	-
3	PERISTAR V I	1.0	Alu. Die Cast	25x25	-	-	41	38	36	33	30	27	23	20	17	13

Starting Method : CSR

S. no	Pump Model	Motor Ratings	Pipe Size Suc x Del.	Total head in Meters											
				6	9	12	15	18	21	24	27	30	33	36	
		HP	mm	Discharge in LPM											
1	PERISTAR V II Plus	0.5	25x25	45	43	40	34	34	31	28	24	20	13@34		
2	PERISTAR VE II Plus	0.5	25x25	45	43	40	34	34	31	28	24	20	13@34		



Subject to technical modification without prior notice.