

► Our technology. Your success.

Pumps ■ Valves ■ Service



PERISTAR GSE

Centrifugal regenerative pump (Slow Speed)



Pumps **Made in India**
with trusted German Technology

PERISTAR GSE

Centrifugal regenerative pump (Slow Speed)

Technical Data

Pump size	: 25 x 25 mm
• Capacity	: up to 3480 LPH
• Head	: up to 36 m
• Power	: up to 0.75 kW (1HP)
• Liquid	: Clear water
• Speed	: 1450 rpm

Applications :

- Booster application
- Lawn sprinklers
- Residential flats, bungalows, recreation clubs

Features:

- Robust and sturdy design
- Single phase operation
- High tensile Bronze impeller for trouble-free operation
- Avon make mechanical seal for long life
- Stainless Steel shaft
- Self priming
- Suction lift up to 8 m
- Sealed for life ball bearings at both ends to take axial as well as radial loads

S. no	Pump Model	Motor Ratings	Starting Method	Pipe Size Suc x Del.	Total head in metres					
		HP(kW)		mm	6	12	18	24	30	36
					Discharge in LPM					
1	Peristar GS I SC	1.0 (0.75)	CSIR	25x25	58	55	50	43	37	18
2	Peristar GSE I	1.0 (0.75)	CSR	25x25	57	48	41	33	27	19
3	Peristar GS II SC	0.50 (0.37)	CSIR	25x25	46	37	29	19	7	-
4	Peristar GSE II	0.50 (0.37)	CSCR	25x25	46	37	29	19	7	-



Subject to technical modification without prior notice.



KSB Limited
Standard Pumps Division
 Plot No. E-3 & E-4, MIDC Sinnar, Nashik - 422 113.
 Tel.: +91-2551-230252 / 253, 229700 www.ksbindia.co.in

Our toll free no : 1800 233 1299
 (Monday to Sunday - 8am to 8pm)

Mktg. Services / 03-22 / 5000