



# PERISTAR GS

Centrifugal Regenerative Pumpset  
(Slow Speed)



E-Warranty QR Code



\* Selected models only



**Pumps Made in India**  
with trusted German Technology

# PERISTAR GS

## Centrifugal Regenerative Pumpset (Slow Speed)

### Technical Data

- Pump size : 25 x 25 mm
- Capacity : up to 58 LPM
- Head : up to 36 meter
- Power : up to 1HP (0.75 kW)
- Liquid : Clear water
- Speed : 1450 rpm

### Applications :

- Lawn Sprinklers
- Water Supply to Overhead Tanks
- Gardens/Fountains
- Construction Site

### Features:

- Robust and sturdy design
- High tensile Bronze impeller for trouble-free operation
- High quality mechanical seal for long life
- Stainless Steel shaft
- Suction lift up to 8 m
- Robust Ball Bearings sealed for long life

Performance Chart : Power supply : 220V, 50 Hz, Single Phase

Sr No	Pump Model	HP	Pipe Size (mm)	Body		Total Head in Meters					
						6	12	18	24	30	36
1	PERISTAR GS II SC	0.5	25x25	CI	LPM	46	37	29	19	7	-
2	PERISTAR GSE II	0.5	25x25	CI		46	37	29	19	7	-
3	PERISTAR GS I SC	1.0	25x25	CI		58	55	50	43	37	18
4	PERISTAR GSE I	1.0	25x25	CI		57	48	41	33	27	19



Subject to technical modification without prior notice.