



PERISTAR SZX

Self priming Monobloc Pumpset



E-Warranty QR Code



*Selected models only



Pumps Made in India
with trusted German Technology

PERISTAR SZ X

Self priming Monobloc Pumpset

Technical Data

- Capacity : up to 2890 LPH
- Head : up to 54 m
- Power : up to 1.1 kW (1.5HP)
- Temperature : Ambient
- Liquid : Clear water
- Speed : 2800 rpm
- Starting Method : CSR

Applications :

- Booster application
- Car washing
- Residential flats, bungalows
- Water circulation in solar systems

Features:

- Single phase operation
- Stainless Steel shaft
- TEFC enclosure
- Fitted with Thermal Overload Protector for safety
- Self priming
- Suction lift up to 6 m
- Dynamically balanced Rotor for longer bearing life and vibration free smooth operation
- Robust Ball Bearings sealed for long life

Performance Chart (Power Supply : 240 V, 50 Hz)

Pump Model	Motor Rating HP (kW)	Pipe Size Suc x Del. (mm)	Total Head in Meters													
			6	9	12	15	18	21	24	27	30	33	36	42	48	54
			Discharge in LPH													
Peristar SZ 05X	0.50 (0.37)	25 X 25	1760	1600	1400	1220	1040	800	480	-	-	-	-	-	-	-
Peristar SZ 07X	0.75 (0.55)	25 X 25	1880	1740	1600	1450	1320	1160	1050	850	660	420 @ 32 mtr	-	-	-	-
Peristar SZ 10X	1.0 (0.75)	25 X 25	2000	1860	1720	1580	1430	1300	1150	1000	800	640	450	-	-	-
Peristar SZ 15X	1.5 (1.1)	25 X 25	2890	2820	2760	2680	2600	2500	2400	2290	2170	2040	1900	1570	1120	550



Subject to technical modification without prior notice.