




PERISTAR V

Self priming Monobloc Pumpset



E-Warranty QR Code



*Selected models only



Pumps Made in India
with trusted German Technology

PERISTAR V

Self priming Monobloc Pumpset

Technical Data

- Pump size : 25 x 25 mm
- Capacity : up to 2700 LPH
- Head : up to 39 m
- Power : up to 1.0 HP (0.75 kW)
- Temperature : Ambient
- Liquid : Clear water
- Speed : 2900 rpm
- Starting Method : CSR

Applications :

- Booster application
- Lawn sprinklers
- Residential flats, bungalows, recreation clubs

Features:

- Robust and sturdy design
- Single phase operation
- High quality mechanical seal for long life
- Fitted with Thermal Overload Protector for safety
- Brass forged impellers for smooth operation
- Self priming
- Suction lift up to 6 m
- Capacitor start and run (PSC) type design eliminates centrifugal switch
- Robust Ball Bearings sealed for long life



Performance Chart (Power Supply : 240 V, 50 Hz)

Sr. no	Pump Model	Motor Rating	Pipe Size	Total Head in Meters											
				6	9	12	15	18	21	24	27	30	33	36	39
		HP (kW)	Suc x Del	Discharge in LPH											
1	Peristar VE II	0.5 (0.37)	25 x 25	2700	2600	2400	2200	2060	1880	1650	1440	1200	-	-	-
2	Peristar V II	0.5 (0.37)	25 x 25	2700	2600	2400	2200	2060	1880	1650	1440	1200	-	-	-
3	Peristar V I	1.0 (0.75)	25 x 25	-	-	2480	2300	2140	1960	1800	1600	1400	1200	1000	800



Subject to technical modification without prior notice.