



# PERISTAR ZDX

## Self Priming Slow Speed Pumps



E-Warranty QR Code



\*Selected models only



**Pumps Made in India**  
with trusted German Technology

# PERISTAR ZDX

## Self Priming Slow Speed Pumps

### Technical Data

- Pump size : 25 x 25 mm
- Capacity : up to 2880 LPH
- Head : up to 45 m
- Power : 0.75 kW (1HP)
- Voltage band : 160 to 260 V
- Temperature : Ambient
- Liquid : Clear water
- Speed : 1440 rpm

### Applications :

- Bungalows, buildings, flats, garages, laundries and industries
- Booster application
- Pumping of water to overhead tank
- Drinking water supply
- Ornamental fountains
- Farmhouses

### Features:

- Monobloc construction
- Single phase operation
- Fitted with Thermal Overload Protector for safety
- Suction lift up to 8 m
- High quality and long life mechanical seal
- Capacitor start and run single phase motor for high torque



### Performance Chart : (Power Supply : 220 V, 50 Hz)

Sr No	Description	HP	Pipe Size (mm)	LPH	Total Head in Metres							
					16	18	22	27	30	36	38	45
1	Peristar ZDX	1	25x25	LPH	2880	2820	2520	2100	1920	1380	1200	600



Subject to technical modification without prior notice.